

M880 RAY CP



APPLICATIONS

- Forestry winches
- Recovery and tow vehicles
- Foggers, fire-fighters
- Forestry equipment
- Special applications



DESCRIPTION

The **RAY CP** radio controls are single-stage pushbutton radio controls without emergency stop. The RAY range has minimal dimensions and an exclusive design that allows functional use in any working condition. The high sensitivity of the buttons guarantees optimal use, even when wearing gloves. The material used for the housing makes this radio control extremely shock-resistant.

All RAY CP transmitters are equipped with 2 LEDs indicating the battery status, the transmitter status and information on any problems with the radio control (very useful for after sales service).

The STOP command is PLC/cat.2/SIL1 level, suitable for all low risk applications.

All the symbols on the control buttons are interchangeable and fully customisable.

TECHNICAL SPECIFICATIONS

Dimensions : 157 x 80 x 44 mm

Housing : Glass fibre reinforced nylon (UL94 HB)

Case colour : Yellow

Degree of protection : IP65

Weight : 360g about (with battery)

Operating range : about 100 m

Operating temperature : -25°C to +70°C

Transmission frequencies : 433.05 to 434.79 MHz (69 channels), 2.4 GHz

Autonomy at 20°C with battery : 25h

Max. number of commands : Depends on the receiver unit

OPTIONS

Data Feedback: Information on the operating status of the tasks on the radio control transmission units. tasks on the radio control transmission units. LED or other display.

Backlit panel.

SUPPLY KIT

- 1 transmitter
- 2 batteries (NiMh)
- 1 ergonomic belt
- 1 receiver mounting kit
- 1 receiver type S, L, H or M
- 1 battery charger
- 1 set of fuses
- 1 user manual
- 1 CE declaration of conformity