

M880 RAY EP



APPLICATIONS

- Forestry winches
- Recovery and tow vehicles
- Foggers, fire-fighters
- Forestry equipment
- Special applications



DESCRIPTION

The RAY EP radio controls include single-stage pushbutton models with emergency stop. The RAY range has minimal dimensions and an exclusive design allowing functional use in any working condition. The high sensitivity of the buttons guarantees optimal use, even when wearing gloves. The material used for the housing makes this radio control extremely shock-resistant.

All RAY EP transmitters are equipped with 2 LEDs to indicate the status of the battery, the transmitter and information on any problems with the radio control (very useful for after-sales service).

All the symbols on the control buttons are interchangeable and fully customisable.

The models are classified in safety category PLe (CAT4) for emergency stop, and PLc (CAT2) for controls with safety STOP activated (UNI EN 954-1 & ISO 13849).

TECHNICAL SPECIFICATIONS

Dimensions : 157 x 80 x 44 mm

Housing : Glass fibre reinforced nylon (UL94 HB)

Case colour : Yellow

Degree of protection : IP65

Weight : 360g about (with battery)

Operating range : about 100 m

Operating temperature : -25°C to +70°C

Transmission frequencies : 433.05 to 434.79 MHz (69 channels), 2.4 GHz

Autonomy at 20°C with battery : 25h

Max. number of commands : Depends on the receiver unit

OPTIONS

Data Feedback: Information on the operating status of the tasks on the radio control transmission units. tasks on the radio control transmission units. LED or other display.

Backlit panel.

SUPPLY KIT

- 1 transmitter
- 2 batteries (LiPo)
- 1 ergonomic belt
- 1 receiver mounting kit
- 1 receiver type S, L, H or M
- 1 battery charger
- 1 set of fuses
- 1 user manual
- 1 CE declaration of conformity