

De 0.12 à 0.70 m<sup>2</sup> d'aire de préhension. Haute qualité, résistantes à l'usure et de bon rapport qualité/prix.



	GBS 12	GBS 16	GBS 22	GBS 22R	GBS 25	GBS 35	GBS 40R	GBS 50R	GBS 70R
Poids	40 kg	50 kg	95 kg	105 kg	170 kg	220 kg	270 kg	280 kg	530 kg
Charge maxi	600 kg	1000 kg	1400 kg	1800 kg	4000 kg	5000 kg	6000 kg	7000 kg	8000 kg
Aires	0.12m <sup>2</sup>	0.16 m <sup>2</sup>	0.22 m <sup>2</sup>	0.22 m <sup>2</sup>	0.25 m <sup>2</sup>	0.35 m <sup>2</sup>	0.40 m <sup>2</sup>	0.50 m <sup>2</sup>	0.70 m <sup>2</sup>
Pression	200 bar	200 bar	200 bar	200 bar	240 bar	240 bar	240 bar	240 bar	240 bar
Débit maximal	30 l/min	40 l/min	50 l/min	50 l/min	75 l/min	75 l/min	75 l/min	75 l/min	75 l/min
A	740 mm	925 mm	1290 mm	1290 mm	1470 mm	1855 mm	1855 mm	2100 mm	2710 mm
B	305 mm	405 mm	520 mm	520 mm	510 mm	633 mm	633 mm	650 mm	930 mm
C	35 mm	40 mm	90 mm	90 mm	90 mm	125 mm	125 mm	100 mm	110 mm
C1	460 mm	550 mm	550 mm	550 mm	650 mm	650 mm	650 mm	650 mm	870 mm
Cl	235 mm	260	315 mm	315 mm	420 mm	470 mm	470 mm	540 mm	560 mm
D	∅	∅	∅	173/4	173/6	173/6	173/6	173/6	173/6
E	50/60/69	50/60/69	173/4	140/4	140/4	140/4	140/4	140/4	140/4