




Hooks for Rotator

	Type	A	B	C	D	E	F	G	Hook only capacity (T)	Lifting capacity (kg)	Weight (kg)	Price
	CFS 4/50	270	55	104	43	35	50	25	5.3	4	5.2	Contact us
	CFS 5/59	280	73	115	43	35	60	30	5.3	5.3	6.8	
	CFS 5/59 D26	280	73	115	43	35	60	26	5.3	4	6.8	
	CFS 5/68-69	283	73	118	43	35	70	30	5.3	5.3	6.8	
	CFS 5/xx	283	73	118	43	35	XX	30	5.3	5.3	6.8	
	CFS 6/59	370	73	128	50	57	60	30	7.5	6	9.5	
	CFS 6/59 D26	370	73	128	50	57	60	26	7.5	6	9.5	
	CFS 6/68-69	370	73	125	50	57	70	30	7.5	6	11	
CFS 6/xx	370	73	125	50	57	XX	30	7.5	6	11		

Mobile hooks for ROTATORS

	CMS 5/xx	(xx = Rotator pin diameter)							5.3	12	Contact us
	CMS 6/xx	(xx = Rotator pin diameter)							6	15	

Quick coupling for orbital rotator with tenon

	Type	Description	Price in € HT
	CAS 00	Complete Quick Coupling Device with screw-on quick couplers	Contact us
	CAS 01M	Upper part (to be mounted on the rotator pin)	
	CAS 01 CA	Removable female part of the quick coupling (pair)	
	CAS 02 CA	Removable male part (rotator) of the quick coupler (pair)	
	CAS 02	Female lower part (to be mounted on the accessory)	
	CAS 04	Spacer 140x140	
	CAS 03	Rigid hook	