

AG Compact Series / 2-hose hydraulic hose reels



References	A	B	D	E	F	With hoses R7-R8-B1		With hoses B2		
	In mm					Ø	Length		Length	
							Total in m	Useful in m	Total in m	Useful in m
AGD200.05.XX	133	65	200	30	195	3/16"	2.5	2.3	-	-
AGD296.06.XX						1/4"	1.5	1.3	-	-
AGD296.05.XX	141	75	235	30	228	3/16"	3.0	2.7	-	-
AGD296.06.XX						1/4"	2.2	1.9	-	-
AGD321.08.XX						5/16"	2.0	1.7	-	-
AGD321.10.XX						3/8"	2.0	1.7	-	-
AGD321.10.XX						1/2"	1.2	0.9	-	-
AGD321.10.XX	-	-	-	-	-					
AGD321.05.XX	154	75	275	30	272	3/16"	4.5	4.2	-	-
AGD341.06.XX						1/4"	4.0	3.7	-	-
AGD341.08.XX						5/16"	3.2	2.9	2.6	2.3
AGD341.10.XX						3/8"	2.8	2.5	2.5	2.2
AGD341.10.XX										
AGD341.06.XX	160	75	295	35	272	1/4"	4.7	4.4	-	-
AGD370.08.XX						5/16"	4.2	3.9	3.5	3.2
AGD370.10.XX						3/8"	3.6	3.3	3	2.7
AGD370.06.XX	160	82	325	37	272	1/4"	5.5	5.2	-	-
AGD370.08.XX						5/16"	5.0	4.7	4.0	3.7
AGD400.10.XX						3/8"	4.5	4.2	4	3.7
AGD400.06.XX	160	82	340	37	272	1/4"	6.0	5.7	-	-
AGD400.08.XX						5/16"	5.3	5	4.5	4.2
AGD400.10.XX						3/8"	4.6	4.3	4.3	4

Max flow rate: 30 l/min
 Working pressure: 300 bar
 Max hose speed: 30 m/min
 Temperature range: -20/+80°C

AGD295 = modello destro/right model - AGS295 = modello sinistro/left model

MOUNTING POSITIONS
OK OPTIONAL

DESTRO
RIGHT

Supporto non disponibile per AGD200
 Support not available on AGD200

2x3/8"
2x1/4" on AGD230.06

Detailed technical drawing of the hose reel with dimensions: A, B, D, E, F, Ø11, 42,5, 40, 148, 55, 80, 12. Labels include 'Destro Right', 'HOSE', and 'Supporto non disponibile per AGD200'.

Pressure : 350 bar with B2 hoses
Also available as left-hand outlet AGS