

## Fixed stabilisers

References	Crane T/m	R*Max (daN)	Weight in Kg	A	C	h*b	D		E	M	S	Overall length of folded cylinder	Options		
							Min	Maxi					Swivel foot	Pilot valve	
A151600	6>15	3750	60	1600	X	120X80	155	410	330	70	35	513	<b>Optional</b>	<b>Optional</b>	
A101800	6>10	3000	65	1800	X	120X80	140	395	330	70	35	513			
A102000	6>10	2500	80	2000	X	120X80	165	475	400	70	35	582			
A222000	13>22	5600	115	2000	X	180X100	205	510	450	85	45	670			
A222000-ROT	13>22	5600	115	2000	X	180X100	567	567	450	85	45	727			Standard
A362100	18>36	7550	150	2100	X	200X100	250	800	550	95	55	840			Standard
A362120	18>36	7550	150	2100	x	200X100	250	650	550	95	55	690			

## Mechanical extension stabilizers

References	Crane T/m	R*Max (daN)	Weight in Kg	A	C	h*b	D		E	M	S	Overall length of folded cylinder	Options	
							Min	Maxi					Swivel foot	Pilot valve
B062600	3>6	1350	90	1600	2600	120X80	170	425	330	70	35	534	<b>Optional</b>	<b>Optional</b>
B062600ROT	3>6	1350	90	1600	2600	120X80	419	419	330	70	35	534		
B062800	3>6	1600	90	1800	2800	120X80	170	425	330	70	35	540		
B062820	3>6	1600	90	1800	2800	120X80	170	325	330	70	35	440		
B103300	6>10	3000	120	2100	3300	150X100	150	459	330	70	35	610		
B263300	14>26	6500	180	2100	3300	204X102	195	500	400	85	45	700		
B263320	14>26	6500	180	2100	3300	204X102	195	360	450	85	45	560		
B263320ROT	14>26	6500	180	2100	3300	204X102	494	49	450	85	45	560		
B264400	14>26	6600	290	2100	4400	200X200	195	500	450	85	45	700		
B264420	14>26	6600	290	2100	4400	200X200	195	360	450	85	45	560		
B403300	19>40	9100	235	2100	3300	202X120	265	665	550	95	55	865		
B403320	19>40	9100	235	2100	3300	202X120	265	515	550	95	55	715		
B404700	19>40	9100	380	2100	4700	206X234	275	665	550	95	55	870	Standard	
B404720	19>40	9100	380	2100	4700	206X234	275		550	95	55	720	Standard	

